



SERIES

ThinLINE Low Profile Break-out Wrench



PRODUCT DETAILS

- Designed to fit tight spaces with ease, provides strength and dependability to get the job done everytime without breaking
- Self-contained, semi-ratcheting mechanism that's not susceptible to breakage
- Delivers sixty degree nut turn before wrench reset it needed
- Interchangeable Wrench heads and reaction units
- Fits tight spaces
- Torque in push and pull modes
- Wrench assemblies include wrench heads and reaction unit; Available to fit metric and standard nut sizes

PRODUCT ATTRIBUTES

Product			
TLH704-24	187.41 N·m	138,230 lbf·ft	5-3/4 in
TLH500-12	56.73 N·m	41,840 lbf·ft	4-5/8 in
TLH506-12	56.73 N·m	41,840 lbf·ft	
TLH506-18	92.79 N·m	68,440 lbf·ft	4-1/4 in
TLH512-18	92.79 N·m	68,440 lbf·ft	4-5/8 in
TLH602-18	92.79 N·m	68,440 lbf·ft	5 in
TLH602-24	187.41 N·m	138,230 lbf·ft	5-3/8 in
TLH608-24	187.41 N·m	138,230 lbf·ft	
TLH614-24	187.41 N·m	138,230 lbf·ft	5-3/8 in
TLH410-12	56.73 N·m	41,840 lbf·ft	4-1/4 in
TLH710-24	187.41 N·m	138,230 lbf·ft	6-1/8 in
TLH800-24	187.41 N·m	138,230 lbf·ft	
SERIES 150-4	4.406 N·m	3,240 lbf·ft	6-1/8 in
SERIES 200-6	11.71 N·m	8,640 lbf·ft	6-1/2 in
SERIES 250-9	27.45 N·m	20,250 lbf·ft	6-7/8 in
SERIES 325-12	56.73 N·m	41,840 lbf·ft	7-1/4 in
SERIES 325-18	92.79 N·m	68,440 lbf·ft	7-5/8 in
SERIES 400-24	187.41 N·m	138,230 lbf·ft	8 in
TLH215-6	11.71 N·m	8,640 lbf·ft	2-9/16 in
TLH107-4	4.406 N·m	3,240 lbf·ft	1-1/4 in
TLH110-4	4.406 N·m	3,240 lbf·ft	1-7/16 in
TLH113-4	4.406 N·m	3,240 lbf·ft	1-5/8 in
TLH200-4	4.406 N·m	3,240 lbf·ft	1-13/16 in
TLH203-6	11.71 N·m	8,640 lbf·ft	2 in
TLH206-6	11.71 N·m	8,640 lbf·ft	
TLH209-6	11.71 N·m	8,640 lbf·ft	2-3/16 in
TLH212-6	11.71 N·m	8,640 lbf·ft	2-3/8 in
TLH104-4	4.406 N·m	3,240 lbf·ft	
TLH302-6	11.71 N·m	8,640 lbf·ft	2-3/4 in
TLH215-9	27.45 N·m	20,250 lbf·ft	2-15/16 in
TLH302-9	27.45 N·m	20,250 lbf·ft	3-1/8 in
TLH308-9	27.45 N·m	20,250 lbf·ft	
TLH314-9	27.45 N·m	20,250 lbf·ft	2-15/16 in
TLH404-9	27.45 N·m	20,250 lbf·ft	3-1/8 in
TLH410-9	27.45 N·m	20,250 lbf·ft	3-1/2 in
TLH404-12	56.73 N·m	41,840 lbf·ft	3-7/8 in